



### **Overview**

Sav182D Power Supply provides 12VDC distributed via eighteen (18) Class 2 Rated PTC protected power-limited outputs for powering surveillance cameras.



### **Specifications**

#### ***Input:***

- 115VAC 60Hz, 3 amp /230VAC 50Hz, 1.5 amp.

#### ***Output:***

- 12VDC @ 11 amp total output current  
(0.61 amp per device, 2.5 amp max.).
- Eighteen (18) Class 2 Rated PTC protected power-limited outputs.
- Filtered and electronically regulated outputs.
- Short circuit and thermal overload protection.

#### ***Electrical:***

- Operating temperature: 0° C to 49° C ambient.
- 68.24 BTU/Hr.
- System AC input VA requirement:
  - 115VAC: 345VA.
  - 230VAC: 330VA.

#### ***Features:***

- Eighteen (18) power LEDs.
- Field installable 3-wire line cord with integral strain relief.
- Unit maintains camera synchronization.
- Ease of installation saves time and eliminates costly labor.

#### ***Mechanical:***

- NEMA1 enclosure.
- Enclosure Dimensions (H x W x D approx.):  
13.5" x 13" x 3.25" (342.9mm x 330.2mm x 82.55mm).
- Product weight (approx.): 7.8 lbs. (3.54 kg).
- Shipping weight (approx.): 8.7 lbs. (3.95 kg).

### **Agency Approvals**



UL Listed for Commercial CCTV Equipment  
(UL 2044).



CUL Listed - CSA Standard C22.2  
No.1-98, Audio, Video and Similar  
Equipment.

**Enclosure Dimensions (H x W x D approximate):**  
 13.5" x 13" x 3.25" (342.9mm x 330.2mm x 82.55mm)

