

MODEL SREX-100

ACTIVE FOCUSED INFRARED



- UL 294 ULC-S319 listed as an access control device
- Narrow activation zone is limited to the door handle area
- Designed to eliminate cross traffic activation
- Cannot be deceived by placing objects under the door
- Easy installation and adjustable depth zone
- Operates on 12 or 24 volts AC or DC auto sensing
- Maximum current draw is 155mA sounder off, 200mA sounder on
- Temperature range for UL installations is +32°F to +120°F, (0°C to +49°C)
- Double pole – double throw contacts (2 form C)
- Relay contact rating is 1.3A @ 30 volts DC or 24 volts AC
- Adjustable time delay from one to sixty seconds
- Built-in buzzer can be silenced if required
- REX input, keypad or card reader input and door position switch input
- 14 pin female connector with four feet of cable
- Three year warranty



Alarm Controls
19 Brandywine Drive
Deer Park, New York 11729
(800) 645-5538
www.alarmcontrols.com

ASSA ABLOY, the global leader
in door opening solutions

FEATURES	ALARM CONTROLS SREX-100	BOSCH DS160	KANTECH T.REX-XL2
IMMUNE TO OBJECTS PLACED UNDER DOOR	YES	NO	NO
TECHNOLOGY	ACTIVE FOCUSED INFRARED	PASSIVE DIFFUSED INFRARED	PASSIVE DIFFUSED INFRARED
PARALLEL TRAFFIC REJECTION	YES	NO	NO
EASY DETECTION ZONE ADJUSTMENT	YES POTENTIOMETER TUNING	NO PLASTIC WEDGE PLACEMENT	NO LOUVER DIRECTION SCREWS
ELECTRIC SPIKE PROTECTION	YES PROVIDED IN SENSOR	NO MUST PROVIDE YOUR OWN	YES PROVIDED IN SENSOR
2 AMP. RELAY CONTACTS	YES S.P.D.T. 2 AMP. CONTACTS	NO S.P.D.T. 1 AMP. CONTACTS	NO S.P.D.T. 1 AMP. CONTACTS
FULLY ADJUSTABLE RELAY HOLD TIME	YES POTENTIOMETER 0 TO 60 SEC.	NO PRESET TIME SETTINGS	NO JUMPER SETTINGS
WIRE HARNESS SUPPLIED	YES	NO	NO
SIMPLE FEATURE SELECTION	YES DIP SWITCHES FOR EACH FEATURE	NO COMBINATION OF OF DIP SWITCHES	YES LIMITED FEATURES
REQUEST TO EXIT INPUT	YES	NO	NO
RELAY MODE FAIL-SAFE/FAIL-SECURE	YES	YES	NO
SOUNDER	YES ADJUSTABLE VOLUME	YES ADJUSTABLE VOLUME	YES NO ADJUSTABLE VOLUME
CARD OR KEYPAD INPUT	YES	YES	NO
CARD SOUNDER ENABLE	YES	YES	NO