

Heavy-Duty, Reliable Control

Norton<sup>®</sup> ASSA ABLOY

ASSA ABLOY, the global leader in door opening solutions



#### 9500 SERIES CAST IRON DOOR CLOSER



Ideal for high use openings, the Norton 9500 Series Cast Iron door closer offers the durability, flexibility and strength required to meet the needs of your facility. For interior or exterior doors, this ANSI/ BHMA Grade 1 closer features a clean, modern cover aesthetic and durable cast iron body that can be used in a variety of institutional environments requiring ADA compliance.

# Benefits

## Reliable

- One-piece cast iron closer body provides strength and durability
- Forged arms for high-use environments
- Independent latch, sweep and backcheck intensity valves to ensure positive latching
- Staked valves offer vandal resistance

## Flexible

- Modern cover aesthetics blend with any decor
- Choice of standard or heavy-duty arms and adjustable spring power meets needs of any application
- Non-handed

# Low Total Cost of Ownership

- Closer mounting bracket provides quick and easy installation
- Pressure relief valves protect the door and frame from damage and reduces maintenance costs
- Exceeds 25 million cycles (witnessed and verified by UL)
- 25-year limited warranty

## Sustainability

- Exceeds 25 million cycles for fewer replacements and less material used
- ABS covers provide PVC-free choice for green building standards
- Covered by Norton End-of-Life Recycling Program

Norton Door Controls 3000 Highway 74 East • Monroe, NC 28112 Tel: 1-877-974-2255 • Fax: 1-800-338-0965

Norton® and Tri-style® are registered trademarks of Yale Security Inc., an ASSA ABLOY Group company. These materials are protected under U.S. copyright laws. All contents current at time of publication. Copyright © 2013-2015, Yale Security Inc., an ASSA ABLOY Group company. All rights reserved. Reproduction in whole or in part without the express written permission of Yale Security Inc. is prohibited.

# **Features**

- One-piece cast iron closer body
- Forged standard and heavy duty arms available as hold open or non-hold open
- Closer mounting installation bracket
- Adjustable spring sizes 1 6
- Maximum degree of swing is 180°, trim permitting
- Tri-style® packaging: regular, top jamb or parallel mounting
- Non-handed
- Pressure relief valves
- Molded ABS plastic cover
- Optional delayed action feature
- 25-year limited warranty
- Exceeds 25 million cycles (witnessed and verified by UL)

- Code Compliance

  Certified to ANSI/BHMA standard A156.4, Grade 1
- Meets the requirements for UL10C for 3-hour assemblies
- Meets requirements for Americans with Disabilities Act (ADA) and ANSI/BHMA standard A117.1

# **Applications**

For high-use openings or those that must meet ADA requirements in:

- Schools/Universities
- Office Buildings
- Healthcare Facilities

43269-3/15R