

The global leader in  
door opening solutions

## Rockwood 556WS - Windstorm Flush Bolt



### Available Finishes:

- US26D/626

#### SIZE:

Face

Plate: 1" x 6 3/4" x 1/8"

Rod: 12" x Ø 1/2"

Mortise

Body: 1" x 5 1/4" x 1 3/8"

Strike: 15/16" x 2 1/4"

Guide: 1" x 2"

#### WEIGHT:

2.5 lbs./2

#### ANSI A156.16:

L04251

### Specifications:

#### MATERIAL:

Brass, Stainless Steel

#### FEATURES:

- 3/4" Bolt Throw, 3/4" Rod Backset
- 12" Stainless Steel Rod Length (Center of Face to Bolt End- Retracted)
- 1 1/2" Adjustable Bolt Head

#### STANDARDS:

- Meets ANSI A156.16, L04251
- UL Certified
- Assembly Approved for Use in the State of Florida, Including the High Velocity Hurricane Zone (HVHZ)
- Fire Rated up to and Including 3 Hours

#### FASTENERS:

8 ea. #8-32 x 1/4" Flat Head Machine Screws in Stainless Steel



300 Main Street  
Rockwood, Pennsylvania 15557  
P: 800.458.2424 • F: 800.922.9212  
www.rockwoodmfg.com • orders.rockwood@assaabloy.com

Copyright © 2017, Rockwood Manufacturing Company, an ASSA ABLOY Group company. All rights reserved. Reproduction in whole or in part without the express written permission of Rockwood Manufacturing Company is prohibited.