

# UL LISTED MAGLOCKS WITH DS

MAGLOCKS WITH ADJUSTABLE RELOCK TIME DELAY, LOCK STATUS SENSOR & DOOR STATUS SENSOR



## PRIMARY APPLICATIONS



## DESCRIPTION

BEA's UL Listed MAGLOCK with DS provides a standards compliant locking solution for retail, healthcare, banking and other high security facilities that require a UL listed security product. UL Listed MAGLOCKS can be used on hollow metal, wood, aluminum, glass and composite door materials.

The MAGLOCK with DS is available in surface mount, single or double door configurations, with a holding force of 600 or 1,200 lbs. These locks include an adjustable zero to 90 second relock time delay, lock status sensor with visible LED and door status sensor.

## FEATURES & BENEFITS

- UL Listed
- Adjustable zero to 90 second relock time delay
- Lock Status Sensor with visible LED
- Door Status Sensor
- Input voltage of 12 / 24 VDC, must be used with UL Listed power supply
- Variety of mounting hardware available
- Available in access control packages with sensor, logic module, actuator and MAGLOCK



BEA, Inc.  
RIDC Park West  
100 Enterprise Drive  
Pittsburgh, PA 15275-1213

Customer Service: 800.523.2462  
Technical Support: 800.407.4545  
www.BEAinc.com

## TECHNICAL SPECIFICATIONS

### 10MAGLOCK3ULDS

<b>Door Configuration</b>	Single, surface mount
<b>Holding Force</b>	600 lb
<b>Input Voltage</b>	12 / 24 VDC (UL Listed power supply required)
<b>Current Draw</b>	0.50 A @ 12 VDC 0.25 A @ 24 VDC
<b>Dimensions</b>	9.84 in (W) × 1.65 in (H) × 1.02 in (D)
<b>Relock Time Delay</b>	0 s – 90 s
<b>Sensor</b>	Lock Status Sensor, Door Status Sensor
<b>Output Relay</b>	Up to 1 A @ 24 VDC

### 10MAGLOCK6ULDS

<b>Door Configuration</b>	Double, surface mount
<b>Holding Force</b>	600 lb
<b>Input Voltage</b>	12 / 24 VDC (UL Listed power supply required)
<b>Current Draw</b>	1 A @ 12 VDC 0.50 A @ 24 VDC
<b>Dimensions</b>	19.76 in (W) × 1.65 in (H) × 1.02 in (D)
<b>Relock Time Delay</b>	0 s – 90 s
<b>Sensor</b>	Lock Status Sensor, Door Status Sensor
<b>Output Relay</b>	Up to 1A @ 24 VDC

### 10MAGLOCK1ULDS

<b>Door Configuration</b>	Single, surface mount
<b>Holding Force</b>	1200 lb
<b>Input Voltage</b>	12 / 24 VDC (UL Listed power supply required)
<b>Current Draw</b>	0.50 A @ 12 VDC 0.30 A @ 24 VDC
<b>Dimensions</b>	10.47 in (W) × 2.87 in (H) × 1.58 in (D)
<b>Relock Time Delay</b>	0 s – 90 s
<b>Sensor</b>	Lock Status Sensor, Door Status Sensor
<b>Output Relay</b>	Up to 1 A @ 24 VDC

### 10MAGLOCK5ULDS

<b>Door Configuration</b>	Double, surface mount
<b>Holding Force</b>	1200 lb
<b>Input Voltage</b>	12 / 24 VDC (UL Listed power supply required)
<b>Current Draw</b>	1 A @ 12 VDC 0.60 mA @ 24 VDC
<b>Dimensions</b>	20.94 in (W) × 2.87 in (H) × 1.58 in (D)
<b>Relock Time Delay</b>	0 s – 90 s
<b>Sensor</b>	Lock Status Sensor, Door Status Sensor
<b>Output Relay</b>	Up to 1 A @ 24 VDC

## RELATED PRODUCTS



**10MAGLOCK3ULDS**  
600 LB, SINGLE



**10MAGLOCK6ULDS**  
600 LB, DOUBLE



**10MAGLOCK1ULDS**  
1200 LB, SINGLE



**10MAGLOCK5ULDS**  
1200 LB, DOUBLE



**10LZBRMAG3UL**  
L & Z BRACKET  
FOR 600 LB, SINGLE



**10LZBRMAG1UL**  
L & Z BRACKET  
FOR 1200 LB, SINGLE



**10MAG6LZUL**  
(2) L & Z BRACKET  
FOR 600 LB, DOUBLE



**10MAG5LZUL**  
(2) L & Z BRACKET  
FOR 1200 LB, DOUBLE



**10UBRACKETUL**  
GLASS DOOR  
MOUNTING KIT



**10FILLER14UL**  
0.25 × 0.75 INCH  
FILLER PLATE



**10FILLER12UL**  
0.50 × 0.75 INCH  
FILLER PLATE



**10FILLER34UL**  
0.75 × 0.75 INCH  
FILLER PLATE



**10FILLER58UL**  
0.0625 × 0.75 INCH  
FILLER PLATE



**10RIMHOUSING3UL**  
ARMATURE PLATE  
HOUSING, 600 LB



**10RIMHOUSING1UL**  
ARMATURE PLATE  
HOUSING, 1200 LB



**10SPACER3UL**  
VERTICAL SPACER  
BRACKET, 600 LB



**10SPACER1UL**  
VERTICAL SPACER  
BRACKET, 1200 LB

